


Data sheet

L65D5806 - Flex Strip IP68 RGBW 4-in-1

PROLED®

Article name: Flex Strip IP68 RGBW 4-in-1

Article number: L65D5806



Article description:

The PROLED FLEX STRIPS are perfect for indirect lighting, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities.

- RGBW (4 colours in one LED). Pastel colour shades and real white possible.
- High flexibility - adaptable to round shapes.
- Installation with clamps or special glue. The 3M adhesive tape on the strip's backside (self adhesive) is only as fit-up aid.
- IP68 for under water use (power supply cable/end caps IP65 when correctly sealed).
- dimmable, autom. colour change, controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller

Technical:

Mounting type:	Surface-mounted on ceiling	Electric:	
Adjustability:	Fixed	System power:	19.8 W
Controllability:	Dimmable, Colour adjustable	Current:	24 V
Safety:	IP68	Safety class:	3
Temperature range:	-10...45 °C	EEL:	A++ - A
Lifetime:	50.000 h at L80B10	UGR:	-

Shape and dimensions:

Length:	1000 mm
Width:	15 mm
Height:	6 mm
Weight:	-

Status 08.12.2020

Technical amendments and errors reserved.

Light output 1 (LED 3000K - CRI 80):

Lamp type:	LED
Lamp power:	5 W
Total luminous flux:	450 lm
Light efficiency:	90 lm/W
CCT:	3000 K
CRI:	80
Light distribution:	(Symmetrical) Wide flood (half value angle 45°...125°)

Light output 2 (LED Blue):

Lamp type:	LED
Lamp power:	5 W
Total luminous flux:	90 lm
Light efficiency:	18 lm/W
CCT:	-
CRI:	-
Light distribution:	(Symmetrical) Wide flood (half value angle 45°...125°)

Light output 3 (LED Green):



Lamp type:	LED
Lamp power:	4.8 W
Total luminous flux:	420 lm
Light efficiency:	87.5 lm/W
CCT:	7247 K
CRI:	-
Light distribution:	(Symmetrical) Wide flood (half value angle 45°...125°)

Light output 4 (LED Red):

Lamp type:	LED
Lamp power:	5 W
Total luminous flux:	150 lm
Light efficiency:	30 lm/W
CCT:	-
CRI:	-
Light distribution:	(Symmetrical) Wide flood (half value angle 45°...125°)

Data sheet

L65D5806 - Flex Strip IP68 RGBW 4-in-1



Distance	Cone diameter	1110lm	E(0°)	E(C90)	E(C0)
0.5	2.11 1.71	1042	64.6°	41	67
1.0	4.21 3.42	261	64.6°	10	17
1.5	6.32 5.13	116	64.6°	5	7
2.0	8.42 6.85	65	64.6°	3	4
2.5	10.53 8.56	42	64.6°	2	3
3.0	12.64 10.27	29	64.6°	1	2

Distance Cone diameter Illuminance

— C0/C180 (Half-peak divergence: 119.4°)
— C90/C270 (Half-peak divergence: 129.2°)

Glare evaluation according to UGR

	70	70	50	50	30	30	70	70	50	50	30		
p Ceiling	50	30	50	30	30	50	30	50	30	30	30		
p Walls	50	30	50	30	30	50	30	50	30	30	30		
p Floor	20	20	20	20	20	20	20	20	20	20	20		
Room size	Viewing direction at right angles to lamp axis						Viewing direction parallel to lamp axis						
X	Y												
2H	2H	23.2	24.6	23.5	24.9	25.1	24.3	25.7	24.7	26.0	26.3		
2H	3H	24.7	25.9	25.0	26.2	26.5	26.5	27.7	26.8	28.0	28.3		
2H	4H	25.2	26.4	25.6	26.7	27.0	27.5	28.7	27.9	29.1	29.4		
2H	6H	25.5	26.6	25.9	27.0	27.3	28.7	29.8	29.0	30.1	30.5		
2H	8H	25.6	26.7	26.0	27.0	27.4	29.2	30.3	29.6	30.7	31.0		
2H	12H	25.6	26.7	26.0	27.0	27.4	29.9	30.9	30.3	31.3	31.6		
4H	2H	24.0	25.2	24.4	25.6	25.9	24.9	26.1	25.3	26.4	26.8		
4H	3H	25.7	26.7	26.1	27.1	27.5	27.2	28.2	27.6	28.6	29.0		
4H	4H	26.3	27.3	26.8	27.7	28.1	28.4	29.3	28.8	29.7	30.1		
4H	6H	26.8	27.6	27.3	28.0	28.5	29.7	30.5	30.1	30.9	31.3		
4H	8H	26.9	27.7	27.4	28.1	28.6	30.3	31.1	30.8	31.5	32.0		
4H	12H	27.0	27.7	27.5	28.1	28.6	31.1	31.8	31.5	32.2	32.7		
8H	4H	26.8	27.6	27.3	28.0	28.5	28.6	29.4	29.1	29.8	30.3		
8H	6H	27.5	28.1	28.0	28.6	29.0	30.1	30.7	30.6	31.1	31.6		
8H	8H	27.7	28.2	28.2	28.7	29.2	30.8	31.4	31.3	31.9	32.4		
8H	12H	27.8	28.3	28.3	28.8	29.3	31.7	32.2	32.2	32.7	33.2		
12H	4H	26.9	27.6	27.4	28.1	28.5	28.6	29.3	29.1	29.8	30.3		
12H	6H	27.6	28.2	28.1	28.7	29.2	30.1	30.7	30.6	31.1	31.7		
12H	8H	27.9	28.4	28.4	28.9	29.4	30.9	31.4	31.4	31.9	32.5		

Variation of the observer position for the luminaire distances S

S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.3 / -0.4	+0.2 / -0.2
S = 2.0H	+0.4 / -0.7	+0.3 / -0.4
Standard table	BK06	BK09
Correction summand	10.6	14.8

Correction glare indices referring to 1110lm total luminous flux

Status 08.12.2020

Technical amendments and errors reserved.