




## MODELA

wall light, up/down, 2700K, PHASE, white

The unusually styled MODELA up/down wall light brings the interior design trend for organic shapes into your exterior space. The IP65-certified outdoor lights are available in white, black or with gold accents. The softly curved design creates a sharply defined cone of light that provides warm white (2700 K) and dimmable accents. Ideal for illuminating facades in an elegant, atmospheric and long-lasting way (L80, 50,000h).



## TECHNICAL DATA

Item no.	1007809
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	65
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	95 mA
Safety class	I
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	213
Number of luminaires at LS C16A	213
Level of inrush current	3.44 A
Duration of inrush current	48.4 µs
Temperature at glass (light emission)	58 °C
Stroboscopic effect (SVM)	0.01

## Light Source

1907083	
---------	---

<b>Lumen</b>	800 lm
<b>Colour temperature</b>	2700 Kelvin
<b>Beam angle</b>	60 °
<b>Color</b>	white
<b>CRI</b>	80
<b>LXXBXX data</b>	L80B50
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Width</b>	9.7 cm
<b>Height</b>	20.2 cm
<b>Depth</b>	9 cm
<b>Net weight</b>	0.62 kg
<b>Gross weight</b>	0.663 kg