


Data sheet

L684926HL - Flex Strip IP53 800 HE+ Mono - SWW

PROLED®

Article name: Flex Strip IP53 800 HE+ Mono - SWW

Article number: L684926HL



Article description:

The PROLED FLEX STRIPS are perfect for indirect lighting, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities.

- High efficiency
- High flexibility – adaptable to round shapes.
- Installation with 3M adhesive tape on the strip's backside (self adhesive).
- IP53 only if glued correctly and if the sides are sealed with glue.
- dimmable and controllable via DMX 512, DALI, KNX, 1-10 V, CASAMBI, RF by MULTI power supplies/controller

Technical:

Mounting type:	Surface-mounted on ceiling	Electric:	
Adjustability:	Fixed	System power:	20 W
Controllability:	Dimmable	Current:	24 V
Safety:	IP53	Safety class:	3
Temperature range:	-10...45 °C	EEL:	A++ - A
Lifetime:	50.000 h at L80B10	UGR:	37.11

Shape and dimensions:



Length:	1000 mm
Width:	10 mm
Height:	3 mm
Weight:	-

Status 08.12.2020

Technical amendments and errors reserved.


Light output 1 (LED 2700K - CRI 90):

Lamp type:	LED
Lamp power:	20 W
Total luminous flux:	2400 lm
Light efficiency:	120 lm/W
CCT:	2700 K
CRI:	90
Light distribution:	(Symmetrical) Wide flood (half value angle 45° ... 125°)



Data sheet

L684926HL - Flex Strip IP53 800 HE+ Mono - SWW



Glare evaluation according to UGR

Room size	X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
p Ceiling	70	70	50	50	30	30	70	70	50	50	30	30
p Walls	50	30	50	30	30	30	50	30	50	30	30	30
p Floor	20	20	20	20	20	20	20	20	20	20	20	20
Room size	X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H		32.6	33.9	33.0	34.2	34.6	32.9	34.1	33.3	34.5	34.9
2H	3H		34.3	35.5	34.8	35.9	36.3	34.9	36.0	35.3	36.4	36.9
2H	4H		35.1	36.2	35.5	36.6	37.0	35.8	36.9	36.3	37.3	37.8
2H	6H		35.6	36.6	36.1	37.1	37.5	36.7	37.7	37.2	38.2	38.7
2H	8H		35.8	36.7	36.2	37.2	37.7	37.2	38.1	37.6	38.6	39.1
2H	12H		35.9	36.8	36.4	37.3	37.8	37.6	38.5	38.1	39.0	39.5
4H	2H		33.4	34.5	33.8	34.9	35.4	33.6	34.7	34.0	35.1	35.6
4H	3H		35.3	36.3	35.8	36.7	37.2	35.8	36.7	36.3	37.2	37.7
4H	4H		36.2	37.0	36.7	37.5	38.1	36.9	37.7	37.4	38.2	38.7
4H	6H		36.9	37.6	37.4	38.1	38.7	37.9	38.7	38.5	39.2	39.7
4H	8H		37.1	37.8	37.7	38.3	38.9	38.4	39.1	39.0	39.7	40.2
4H	12H		37.3	37.9	37.8	38.4	39.0	39.0	39.6	39.5	40.1	40.7
8H	4H		36.6	37.3	37.2	37.8	38.4	37.2	37.9	37.8	38.4	39.0
8H	6H		37.5	38.1	38.1	38.6	39.2	38.5	39.0	39.1	39.6	40.2
8H	8H		37.9	38.3	38.5	38.9	39.6	39.1	39.6	39.7	40.2	40.8
8H	12H		38.1	38.5	38.7	39.1	39.8	39.8	40.2	40.4	40.8	41.5
12H	4H		36.7	37.3	37.3	37.9	38.5	37.3	37.9	37.8	38.4	39.0
12H	6H		37.7	38.1	38.2	38.7	39.4	38.6	39.1	39.2	39.6	40.3
12H	8H		38.1	38.5	38.7	39.1	39.8	39.3	39.7	39.9	40.3	41.0
Variation of the observer position for the luminaire distances S												
S = 1.0H	+0.1 / -0.1					+0.1 / -0.1						
S = 1.5H	+0.2 / -0.3					+0.2 / -0.2						
S = 2.0H	+0.3 / -0.5					+0.3 / -0.4						
Standard table	BK07					BK09						
Correction summand	21.1					23.1						
Correction glare indices referring to 2400lm total luminous flux												

Status 08.12.2020

Technical amendments and errors reserved.