





HELIA 60

pendant, LED, 3000K, round, white, flat canopy for recessed installation, 7.5W

With the HELIA 60 you have a recessed pendant with a puristic and clear design. This luminaire is available in black, white and brushed copper. With integrated 7.5 W warm-white premium LED. The luminaire is supplied with a 1.5 m connection lead / suspension. A separate 500mA constant current driver is required for operation.



TECHNICAL DATA

Item no.:	158401
Lamps included	0
Number of different light outlets	1
Secondary power / secondary voltage	500 mA/V
Length	60.0 cm
Pendant length	150.0 cm
Diameter	3.0 cm
Installation diameter	6.8 cm
Installation depth	3.0 cm
Net weight	0.496 kg
Gross weight	0.748 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	7.5 W
Lumen	550 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	>90
Binning	6

Accessories

464091	LED DRIVER , 9VA, 500mA, incl. strain relief
464144	LED DRIVER , 15W, 500mA, incl. strain relief, dimmable

LXXBXX data	70/50
Service life	30000 h
Maximum ambient temperature	30 °C
BIG WHITE Page	126

Notes
