


Data sheet

L711H488+L711HAR1 - High Bay 400 - NW - Refector Alu 45deg

PROLED®

Article name: High Bay 400 - NW - Refector Alu 45deg

Article number: L711H488+L711HAR1



Article description:

LED high bay luminaire for factory buildings, production halls, assembly halls, storage buildings, sales areas, exhibition spaces, ...

Technical:

Mounting type: Suspended

Adjustability: Fixed

Controllability: Dimmable

Safety: IP20

Temperature range: -40...55 °C

Lifetime: 50.000 h at L80B10

Electric:

System power: 400 W

Current: 220-240 V

Safety class: 1

EEL: A++ - A

UGR: 18.82

Shape and dimensions:

Height: 585 mm

Diameter: 420 mm

Weight: 11 kg

Light output 1 (LED 4000K - CRI 80):

Lamp type: LED

Lamp power: 400 W

Total luminous flux: 44500 lm

Light efficiency: 111.2 lm/W

CCT: 4000 K

CRI: 80

Light distribution: (Symmetrical) Medium flood (half value angle 15°...45°)

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany




Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com

Data sheet

L711H488+L711HAR1 - High Bay 400 - NW - Refector Alu 45deg

PROLED®



Glare evaluation according to UGR

p Ceiling	70	70	50	50	30	70	70	50	50	30
p Walls	50	30	50	30	30	50	30	50	30	30
p Floor	20	20	20	20	20	20	20	20	20	20
Room size	X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis		
2H	2H	18.7	19.4	18.9	19.6	19.8	18.7	19.4	18.9	19.6
2H	3H	18.8	19.5	19.0	19.7	19.9	18.8	19.5	19.0	19.7
2H	4H	18.8	19.4	19.1	19.7	19.9	18.8	19.4	19.1	19.7
2H	6H	18.8	19.3	19.1	19.6	19.9	18.8	19.3	19.1	19.6
2H	8H	18.7	19.3	19.1	19.6	19.9	18.7	19.3	19.1	19.6
2H	12H	18.7	19.2	19.1	19.6	19.9	18.7	19.2	19.1	19.6
4H	2H	18.6	19.3	18.9	19.5	19.8	18.6	19.3	18.9	19.5
4H	3H	18.8	19.3	19.1	19.6	19.9	18.8	19.3	19.1	19.6
4H	4H	18.8	19.3	19.2	19.6	20.0	18.8	19.3	19.2	19.6
4H	6H	18.8	19.2	19.2	19.6	20.0	18.8	19.2	19.2	19.6
4H	8H	18.8	19.2	19.2	19.6	20.0	18.8	19.2	19.2	19.6
4H	12H	18.8	19.1	19.2	19.5	19.9	18.8	19.1	19.2	19.5
8H	4H	18.8	19.1	19.2	19.5	19.9	18.8	19.1	19.2	19.5
8H	6H	18.8	19.1	19.3	19.5	19.9	18.8	19.1	19.3	19.5
8H	8H	18.8	19.0	19.3	19.5	19.9	18.8	19.0	19.3	19.5
8H	12H	18.8	19.0	19.3	19.4	19.9	18.8	19.0	19.3	19.4
12H	4H	18.7	19.0	19.2	19.4	19.9	18.7	19.0	19.2	19.4
12H	6H	18.8	19.0	19.2	19.4	19.9	18.8	19.0	19.2	19.4
12H	8H	18.8	19.0	19.3	19.4	19.9	18.8	19.0	19.3	19.4

Variation of the observer position for the luminaires distances S

S = 1.0H	+3.3 / -3.4	+3.3 / -3.4
S = 1.5H	+5.8 / -4.2	+5.8 / -4.2
S = 2.0H	+7.7 / -5.1	+7.7 / -5.1

Standard table	BK01	BK01
Correction summand	0.8	0.8

Correction glare indices referring to 44500lm total luminous flux

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com


Data sheet

L711H488+L711HAR2 - High Bay 400 - NW - Refektor Alu 70deg

PROLED®

Article name: High Bay 400 - NW - Refektor Alu 70deg

Article number: L711H488+L711HAR2



Article description:

LED high bay luminaire for factory buildings, production halls, assembly halls, storage buildings, sales areas, exhibition spaces, ...

Technical:

Mounting type:	Suspended	Electric:	
Adjustability:	Fixed	System power:	400 W
Controllability:	Dimmable	Current:	220-240 V
Safety:	IP20	Safety class:	1
Temperature range:	-40...55 °C	EEL:	A++ - A
Lifetime:	50.000 h at L80B10	UGR:	23.78

Shape and dimensions:

Height:	475 mm
Diameter:	495 mm
Weight:	11 kg

Light output 1 (LED 4000K - CRI 80):

Lamp type:	LED
Lamp power:	400 W
Total luminous flux:	44500 lm
Light efficiency:	111.2 lm/W
CCT:	4000 K
CRI:	80
Light distribution:	(Symmetrical) Wide flood (half value angle 45°...125°)




Status 08.12.2020

Technical amendments and errors reserved.

Data sheet

L711H488+L711HAR2 - High Bay 400 - NW - Refektor Alu 70deg

PROLED®



Glare evaluation according to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
X	Y										
2H	2H	24.2	25.2	24.5	25.4	25.6	24.2	25.2	24.5	25.4	25.6
2H	3H	24.0	24.9	24.3	25.2	25.4	24.0	24.9	24.3	25.2	25.4
2H	4H	24.0	24.8	24.3	25.1	25.3	24.0	24.8	24.3	25.1	25.3
2H	6H	23.9	24.7	24.2	24.9	25.2	23.9	24.7	24.2	24.9	25.2
2H	8H	23.9	24.6	24.2	24.9	25.2	23.9	24.6	24.2	24.9	25.2
2H	12H	23.8	24.5	24.2	24.8	25.1	23.8	24.5	24.2	24.8	25.1
4H	2H	24.1	24.9	24.4	25.2	25.5	24.1	24.9	24.4	25.2	25.5
4H	3H	24.0	24.6	24.3	25.0	25.3	24.0	24.6	24.3	25.0	25.3
4H	4H	23.9	24.5	24.3	24.8	25.2	23.9	24.5	24.3	24.8	25.2
4H	6H	23.8	24.3	24.2	24.7	25.1	23.8	24.3	24.2	24.7	25.1
4H	8H	23.8	24.2	24.2	24.6	25.0	23.8	24.2	24.2	24.6	25.0
4H	12H	23.7	24.2	24.2	24.6	25.0	23.7	24.2	24.2	24.6	25.0
8H	4H	23.8	24.2	24.2	24.6	25.0	23.8	24.2	24.2	24.6	25.0
8H	6H	23.7	24.1	24.1	24.5	24.9	23.7	24.1	24.1	24.5	24.9
8H	8H	23.7	24.0	24.1	24.4	24.9	23.7	24.0	24.1	24.4	24.9
8H	12H	23.6	23.9	24.1	24.4	24.9	23.6	23.9	24.1	24.4	24.9
12H	4H	23.7	24.2	24.2	24.6	25.0	23.7	24.2	24.2	24.6	25.0
12H	6H	23.7	24.0	24.1	24.4	24.9	23.7	24.0	24.1	24.4	24.9
12H	8H	23.6	23.9	24.1	24.4	24.9	23.6	23.9	24.1	24.4	24.9
Variation of the observer position for the luminaire distances S											
S = 1.0H		+1.7 / -1.4					+1.7 / -1.4				
S = 1.5H		+2.9 / -18.4					+2.9 / -18.4				
S = 2.0H		+4.4 / -19.1					+4.4 / -19.1				
Standard table		BK00					BK00				
Correction summand		5.7					5.7				
Correction glare indices referring to 44500lm total luminous flux											

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com


Data sheet

L711H488+L711HAR4 - High Bay 400 - NW - Refl. Polycarbonate

PROLED®

Article name: High Bay 400 - NW - Refl. Polycarbonate

Article number: L711H488+L711HAR4



Article description:

LED high bay luminaire for factory buildings, production halls, assembly halls, storage buildings, sales areas, exhibition spaces, ...

Technical:

Mounting type: Suspended

Adjustability: Fixed

Controllability: Dimmable

Safety: IP20

Temperature range: -40...55 °C

Lifetime: 50.000 h at L80B10

Electric:

System power: 400 W

Current: 220-240 V

Safety class: 1

EEL: A++ - A

UGR: 18.1

Shape and dimensions:

Height: 600 mm

Diameter: 410 mm

Weight: 11 kg

Light output 1 (LED 4000K - CRI 80):

Lamp type: LED

Lamp power: 400 W

Total luminous flux: 44500 lm

Light efficiency: 111.2 lm/W

CCT: 4000 K

CRI: 80

Light distribution: (Symmetrical) Wide flood (half value angle 45°...125°)

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany




Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com

Data sheet

L711H488+L711HAR4 - High Bay 400 - NW - Refl. Polycarbonate

PROLED®



Glare evaluation according to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
X	Y										
2H	2H	17.7	18.5	18.0	18.7	19.0	17.7	18.5	18.0	18.7	19.0
2H	3H	17.9	18.6	18.2	18.9	19.2	17.9	18.6	18.2	18.9	19.2
2H	4H	17.9	18.6	18.3	18.9	19.2	17.9	18.6	18.3	18.9	19.2
2H	6H	17.9	18.5	18.3	18.8	19.2	17.9	18.5	18.3	18.8	19.2
2H	8H	17.9	18.5	18.3	18.8	19.2	17.9	18.5	18.3	18.8	19.2
2H	12H	17.9	18.5	18.3	18.8	19.1	17.9	18.5	18.3	18.8	19.1
4H	2H	17.7	18.4	18.1	18.7	19.0	17.7	18.4	18.1	18.7	19.0
4H	3H	18.0	18.6	18.4	18.9	19.3	18.0	18.6	18.4	18.9	19.3
4H	4H	18.1	18.6	18.5	19.0	19.3	18.1	18.6	18.5	19.0	19.3
4H	6H	18.1	18.5	18.5	18.9	19.3	18.1	18.5	18.5	18.9	19.3
4H	8H	18.1	18.5	18.5	18.9	19.3	18.1	18.5	18.5	18.9	19.3
4H	12H	18.1	18.4	18.6	18.9	19.3	18.1	18.4	18.6	18.9	19.3
8H	4H	18.1	18.4	18.5	18.8	19.3	18.1	18.4	18.5	18.8	19.3
8H	6H	18.1	18.4	18.6	18.8	19.3	18.1	18.4	18.6	18.8	19.3
8H	8H	18.1	18.4	18.6	18.8	19.3	18.1	18.4	18.6	18.8	19.3
8H	12H	18.1	18.3	18.6	18.8	19.4	18.1	18.3	18.6	18.8	19.4
12H	4H	18.0	18.4	18.5	18.8	19.2	18.0	18.4	18.5	18.8	19.2
12H	6H	18.1	18.3	18.5	18.8	19.3	18.1	18.3	18.5	18.8	19.3
12H	8H	18.1	18.3	18.6	18.8	19.3	18.1	18.3	18.6	18.8	19.3
Variation of the observer position for the luminaires distances S											
S = 1.0H		+4.1 / -2.2					+4.1 / -2.2				
S = 1.5H		+6.6 / -3.0					+6.6 / -3.0				
S = 2.0H		+8.5 / -4.0					+8.5 / -4.0				
Standard table		BK01					BK01				
Correction summand		0.1					0.1				
Correction glare indices referring to 44500lm total luminous flux											

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com


Data sheet

L711H488+L711HAR5 - High Bay 400 - NW - Refl. Polycarbonate + Cover

PROLED®

Article name: High Bay 400 - NW - Refl. Polycarbonate + Cover

Article number: L711H488+L711HAR5



Article description:

LED high bay luminaire for factory buildings, production halls, assembly halls, storage buildings, sales areas, exhibition spaces, ...

Technical:

Mounting type: Suspended

Adjustability: Fixed

Controllability: Dimmable

Safety: IP20

Temperature range: -40...55 °C

Lifetime: 50.000 h at L80B10

Electric:

System power: 400 W

Current: 220-240 V

Safety class: 1

EEL: A++ - A

UGR: 19.53

Shape and dimensions:

Height: 600 mm

Diameter: 410 mm

Weight: 11 kg

Light output 1 (LED 4000K - CRI 80):

Lamp type: LED

Lamp power: 400 W

Total luminous flux: 44500 lm

Light efficiency: 111.2 lm/W

CCT: 4000 K

CRI: 80

Light distribution: (Symmetrical) Wide flood (half value angle 45°...125°)

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®

MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany




Phone +49.821.60099-0 | Fax +49.821.60099-99

info@proled.com | proled.com

Data sheet

L711H488+L711HAR5 - High Bay 400 - NW - Refl. Polycarbonate + Cover

PROLED®



Glare evaluation according to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
X	Y										
2H	2H	18.9	19.8	19.2	20.1	20.4	18.9	19.8	19.2	20.1	20.4
2H	3H	19.2	20.0	19.6	20.3	20.7	19.2	20.0	19.6	20.3	20.7
2H	4H	19.2	20.0	19.6	20.4	20.7	19.2	20.0	19.6	20.4	20.7
2H	6H	19.2	19.9	19.6	20.3	20.7	19.2	19.9	19.6	20.3	20.7
2H	8H	19.2	19.9	19.6	20.3	20.7	19.2	19.9	19.6	20.3	20.7
2H	12H	19.2	19.8	19.6	20.3	20.7	19.2	19.8	19.6	20.3	20.7
4H	2H	19.0	19.8	19.4	20.1	20.5	19.0	19.8	19.4	20.1	20.5
4H	3H	19.4	20.0	19.8	20.5	20.9	19.4	20.0	19.8	20.5	20.9
4H	4H	19.5	20.1	20.0	20.5	21.0	19.5	20.1	20.0	20.5	21.0
4H	6H	19.5	20.0	20.0	20.5	21.0	19.5	20.0	20.0	20.5	21.0
4H	8H	19.5	20.0	20.0	20.5	21.0	19.5	20.0	20.0	20.5	21.0
4H	12H	19.5	19.9	20.1	20.4	21.0	19.5	19.9	20.1	20.4	21.0
8H	4H	19.5	19.9	20.0	20.4	20.9	19.5	19.9	20.0	20.4	20.9
8H	6H	19.5	19.9	20.1	20.4	21.0	19.5	19.9	20.1	20.4	21.0
8H	8H	19.6	19.9	20.1	20.4	21.0	19.6	19.9	20.1	20.4	21.0
8H	12H	19.6	19.8	20.2	20.4	21.0	19.6	19.8	20.2	20.4	21.0
12H	4H	19.4	19.8	20.0	20.3	20.9	19.4	19.8	20.0	20.3	20.9
12H	6H	19.5	19.8	20.1	20.3	20.9	19.5	19.8	20.1	20.3	20.9
12H	8H	19.5	19.8	20.1	20.4	21.0	19.5	19.8	20.1	20.4	21.0
Variation of the observer position for the luminaire distances S											
S = 1.0H		+1.9 / -1.3					+1.9 / -1.3				
S = 1.5H		+3.7 / -2.2					+3.7 / -2.2				
S = 2.0H		+5.4 / -3.2					+5.4 / -3.2				
Standard table		BK02					BK02				
Correction summand		2.1					2.1				
Correction glare indices referring to 44500lm total luminous flux											

Status 08.12.2020

Technical amendments and errors reserved.

PROLED®
MBN GmbH | Balthasar-Schaller-Str. 3 | 86316 Friedberg | Germany
Phone +49.821.60099-0 | Fax +49.821.60099-99
info@proled.com | proled.com